



PASTOR – TVORNICA VATROGASNIH APARATA d.d.

OIB: 17140959007; MB: 03919013

Rakitje – 10437 Bestovje, Novačka cesta 2

T: +385 1 3636 455; F: + 385 1 3691 455,

www.pastor.hr; e-mail: prodaja@pastor.hr

Žiro račun: 2402006-1100603308, Erste&Steiermärkische bank d.d., Rijeka, Jadranski trg 3A



Fire extinguisher P1A

Pastor produces fire extinguishers under constant pressure in two forms: portable with a charge of 1, 2, 3, 4, 6, 9 and 12 kg and transportable with a charge of 50 kg of powder.

Thanks to the tank that is under constant pressure of the propellant nitrogen gas and the simple construction, these devices are always ready for use. The built-in pressure gauge, which is supplied as standard with these types of devices, enables insight into the state of the device at any time.

HOW TO USE: When using, pull out the fuse, take the rubber connecting tube in your hands and press the valve handle to start extinguishing. Use the nozzle to direct the powder stream at the base of the fire and, if necessary, stop the flow of powder using the valve handle.

APPLICATION: Fire extinguishers under constant pressure due to their small dimensions and weight are recommended for extinguishing initial fires in vehicles and households.

They can be successfully used for extinguishing all classes of fires except burning metals and their alloys

Stock Number **501005H**

Specification

Performance of the device	portable under constant pressure
Type of extinguishing agent	powder ABC
Fire class	ABC
Edition	Regular Edition
Shutting down electrical installations and devices under voltage	up to 1000V
Amount of extinguishing agent	1 kg
Drive	Nitrogen (N2) – 14 bar / 20°C
Temperature range	- 30°C to +60°C
The weight of the device	2.1 kg
EN3 efficiency	8A 34B C
Efficiency in extinguishing units	2 JG
Dimensions (diameter/height mm)	85 / 290
Standard	EN3
Directives	PED 2014/68/EU